Title: On the Conversion between Non-Binary and Binary Constraint Satisfaction Problems

Authors: F. Bacchus and P. van Beek

Proc: AAAI

Pages: 310–319

Year: 1998

Theory and Practice of Constraint Satisfaction

CSCE 990-05, Fall 1999

www.cse.unl.edu/~choueiry/CSE990-05/

Summary

- Studies 2 mappings of non-binary CSPs into a binary representation { dual dual / hidden variable
- Studies performance of BT search in each mapping vs. its performance in non-binary version
- Considers theoretical & experimental aspects
- Proposes FC^+, yet lookahead strategy
- Indicates interesting open issues

Importance

- Learn about the mappings
- Do you want to carry out a theoretical study to settle the question?
  $\rightarrow$ an opportunity for a term paper

Facts

- Non-binary constraints useful in the modeling of many applications
- Most research in CSPs is restricted to binary constraints
- Generalizing techniques for binary CSPs to address non-binary constraints is not straightforward

  .. but sometimes done: BT+FC & BT+arc-consistency
- Usual work-around/justification: map non-binary constraints into binary ones

Ideally

- Modeling: use the most expressive/natural representation
- Solving: use the most 'effective' representation

PS: the 'effectiveness' of a **representation** per se is a new, and difficult, research area. No clear metrics exist, to my knowledge

Your options

- Directly apply techniques for non-binary CSP
  ...too few :-(
- Translate non-binary→binary, then solve
  Techniques for binary CSPs exploit graph/constraint properties
  Does the translation preserve/yield such properties?
  ...will the translation degrade the performance of the techniques developed for binary CSPs?

Goal

- Study the effect of the translation on the performance of BT search
- Ultimately, establish properties of the translation to legitimize the restriction of research efforts to binary CSPs

Considers two translation methods

Results

- In most cases, the non-binary representation is most effective
- For tight constraints: binary representation wins

Example:

3SAT:

$(X_1 \vee X_2 \vee X_6) \wedge (\bar{X}_1 \vee X_3 \vee X_4) \wedge (\bar{X}_4 \vee \bar{X}_5 \vee X_6) \wedge (X_2 \vee X_5 \vee \bar{X}_6)$

3SAT as a non-binary (ternary) CSP

Variables: $X_1, X_2, \ldots, X_6$

Domains: $D_{X_i} = \{0, 1\}$

Constraints: $C_{126} = \{(0,0,1), (0,1,0), \ldots\}$, except (0,0,0)

C_{134} = all - $\{(1,0,0)\}$

C_{456} = all - $\{(1,1,0)\}$

C_{256} = all - $\{(0,0,1)\}$

BT+FC non-binary constraints

- A k-ary constraint is forward-checkable, if
  - $(k-1)$ of its variables are instantiated
  - one variable uninstantiated
- BT-search:
  - instantiate one variable
  - repeat: for each newly f-checkable constraint, check future variable
  - if any domain is empty, backtrack

Dual-graph representation

Usually: { CSP variable → node ; constraint → hyper-arc 'label' }

Dual graph: { constraint → node (called c-variable) ; CSP variable → arc 'label' }



Constraint: X_1 must have the same value in C_{126} and C_{134}

Domain of a c-variable: constraint definition

Hidden-variable representation

Variables: CSP variables +
1 hidden variable (h-variable) per constraint

Constraints: only between a variable and the h-variables corresponding to its applicable constraints



Constraint: a value of C_{126} correspond to one value of X_1

Domain of the h-variable = domain of the c-variable

Two binary representations

- **Dual graph**

  Nodes = only the constraints

  (CSP variables are not represented)

  Simple arcs between constraints



- **Hidden variable**

  Nodes = CSP variables and constraints

  Simple arcs constraints $\longleftrightarrow$ variables



$\longrightarrow$ Compare to Freuder's constraint graphs

Theoretical comparison

I– Space requirements (data structures)

II– Analytical bounds (#nodes, #checks in search)

I– Space requirements

- Binary representations require additional storing of domains for the c/h-variables (allowed k-tuples for each k-ary constraint)

  FC needs storage space proportional to the size of the domains (i.e., reductions)

  $\rightarrow$ could be substantial

- No space is also needed to store constraints in binary representations: simple projection of an instantiation, can be done in constant time **assuming** domains of c/h-variables are stored extensionally

II– Analytical Bounds

Criteria

- number of visited nodes
- number of checks performed

Working assumption

- checking k-constraint costs k operations
- checking binary constraint costs 2 operations

Comparison

- dual-graph vs. non-binary
- hidden-variable vs. non-binary

Result

- not conclusive (one can always build a case where solving BT+FC has a better performance in one representation than in another)
- experimental evidence needed

Dual graph vs. non-binary CSP (I)

Loose constraint $\Rightarrow$ exponentially large domains for c-variables $\Rightarrow$ non-binary is less costly

Example:

n variables: $X_1, X_2, \ldots X_n$

n constraints: $X_1, \bar{X}_1 \vee X_2, \bar{X}_1 \vee \bar{X}_2 \vee X_3, \ldots, \bar{X}_1 \vee \bar{X}_1 \vee \ldots \bar{X}_n$

Non-binary: n nodes, $\mathcal{O}(n^2)$ consistency checks

Dual-graph: n nodes, $\mathcal{O}(2^n)$ consistency checks

Tight constraint $\Rightarrow \ldots \Rightarrow$ dual-graph is less costly

Example:

n variables: $X_1, X_2, \ldots X_n$

n constraints: $X_1 \wedge \ldots \wedge X_{n-1}, X_1 \wedge \ldots \wedge X_{n-2} \wedge X_n, \ldots, X_2 \wedge \ldots \wedge X_n$

Non-binary: 2^{n-1} nodes, $\mathcal{O}(n2^n)$ consistency checks

Dual-graph: n nodes, $\mathcal{O}(n^2)$ consistency checks

Experiments

Carried out on random CSPs

Results have predictive power verified by:

- random 3SAT
- crossword puzzles

$\longrightarrow$ Reference for a good methodology for experiments

Conclusions

Translating non-binary constraints involves overhead.

Translation is **perhaps** worthwhile if constraints are restrictive

Translation, as a strategy, is justifiable

Many open issues..

→ # tuples in constraints a good indicator? probably..

→ dual graph vs. hidden-variable ?

→ .. we need to study further these translations/reformulations

→ to gain insight for designing good algorithms for non-binary constraints